

PRODUCTS AND EQUIPMENT, INCORPORATED

P. O. BOX 910

HARRISON, ARKANSAS 72802-0910 E-MAIL: claridge@claridgeproducts.com



PHONE: 870-743-2200

FAX: 870-743-1908

CLARIDGE CORK BULLETIN BOARD MATERIAL

SPECIFICATIONS:

All tackboard surface shall be 1/4" Claridge Cork and oxidized linseed oil laminated to a burlap by Claridge Products and Equipment, Inc., Harrison, Arkansas, as follows:

FACE SHEET:

1/4" Claridge Tan Cork, or color as specified by architect

BINDER:

Burlap

GENERAL INFORMATION:

All unmounted Claridge Cork bulletin board material shall be available up to 90'0" in one piece. Standard height is 4'0".

INSTALLATION AND CLEANING:

Shall be in exact accordance with manufacturer's printed instructions.

CHARACTERISTICS:

Self-healing, soil resistant, washable surface. Dimensionally stable all directions. Contains no harmful by-products or carcinogens.

ASTM E-84 (Fuel Contribution) - Class B; NFPA255 (Critical Radiant Flux) - Class II. QUALITY ASSURANCE:

All Claridge Cork Bulletin Board is made from pure natural ingredients that combine under heat and pressure to create a smooth, uniformly dense, suede-like surface.

GUARANTEE:

Under normal usage and maintenance, and when installed in accordance with Claridge instructions and recommendations, Claridge Cork Bulletin Boards are guaranteed for one year against any defects in material and workmanship,