

2115
11/1/07

DIVISION 10 - SECTION 10100 / DIVISION 12 - SECTION 12350

PART 1 - GENERAL

- 1.01 DESCRIPTION OF WORK
- A. This section includes **Premiere Freestanding Trophy and Display Cases**
 - B. This section includes **No. 334 Universal Freestanding Trophy and Display Cases**
- 1.02 REFERENCED STANDARDS
- A. **ASTM-E 84**
 - B. **ASTM B221**
- 1.03 SUBMITTALS
- A. **Shop Drawings:** Provide shop drawings for each type of freestanding display or trophy case required.
 - B. **Product Data:** Provide technical data for materials specified. Include Material Safety Data Sheets, when applicable.
 - C. **Samples:**
 - 1. **Manufacturer's color charts**
 - 2. **Composition samples of material and trim to illustrate finish, color and texture.**
- 1.04 OPERATION & MAINTENANCE
- A. **Include data on regular cleaning, stain removal, and precautions.**
- 1.05 REGULATORY REQUIREMENTS
- A. **Conform to applicable code for flame/smoke rating in tackboards in accordance with ASTM-E 84.**
- 1.06 QUALITY ASSURANCE
- A. **Provide all items in this section as manufactured by:**
Claridge Products and Equipment, Inc.
Harrison, Arkansas 72602-0910
Phone: 870/743-2200; Fax: 870/743-1908
- 1.07 FIELD CONDITIONS
- A. **Field measure prior to preparation of shop drawings and fabrication to ensure proper fit.**
- 1.08 WARRANTY
- A. **Submit a standard warranty, stating when installed in accordance with manufacturer's instructions and recommendations, Claridge trophy and display cases are guaranteed for one year against defects in materials and workmanship. Guarantee does not cover normal wear and tear, improper handling, any misuse, or any defects caused by vandalism or subsequent abuse. Guarantee covers replacement of defective material but does not include cost of removal or reinstallation.**

PART 2 - PRODUCTS

2.01 MANUFACTURERS

- A. Premiere Freestanding Display and Trophy Cases as manufactured by: Claridge Products and Equipment, Inc., Harrison, Arkansas 72602-0910; Phone: 870-743-2200; Fax: 870-743-1908

2.02 MATERIALS

- A. Premiere Freestanding Trophy and Display Cases
1. Architect to select from Claridge Cork, Fabricork, Hook-Fab, Designer Fabric and Tan Nucork tackable back panel or Walnut or Oak grained low-pressure laminate finish back panel.
 2. Standard sizes: 4'x4'; 4' x 5'; 4'x6'; 4'x8'; 4'x10'; 4'x12'; 4'x16'. Special sizes on request.
 3. Housing: Perimeter trim is 1-1/2" x 2" extruded aluminum tube; inside case depth 13-3/4"; O.A. 16".
 4. Floor leveling glides included.
- B. Glass Doors: Glass doors are 3/16" tempered, unless otherwise specified.
1. Sliding door cases have ground-in finger pulls, doors slide on glides, and are fitted with flat key tumbler locks
 2. Three 6, 8, 10 or 12-inch wide (as specified) adjustable glass shelves
 3. Necessary brackets and shelf standards provided.
- C. Legs or Bases: Freestanding cases are 5'6" O.A.; legs or bases are 18" high. Base panels available with walnut or oak grained finish low-pressure laminate.
- D. Metal Trim and Accessories: Provide aluminum extrusions as manufactured by Claridge Products and Equipment, Inc. Trim shall be heavy gauge extruded aluminum and shall meet or exceed ASTM B221 Alloy Standards. Finish to be etched and anodized satin finish.
- E. Colors: As selected from manufacturer's standard colors. Over 50 standard tackboard colors to choose from. Color charts furnished on request.
- F. Options: Color anodize or powder coat finish on trim; fluorescent lights
- G. Universal No. 334 Freestanding Display Case
1. Glass back panel standard. (No. 335 has oak grain low pressure laminate back panel)
 2. Standard size: 72" (H); 48" (W); 18" (D)
 3. Five adjustable glass shelves with brackets
 4. Low pressure laminate base panel in oak finish is 18" high

2.03 FABRICATION

- A. Shop assembly: Provide factory assembled cases to requirements indicated on shop drawings.
- B. Units shall be of dimensions shown in details and in accordance with manufacturer's shop drawings, as approved by architect.

PART 3 - EXECUTION

3.01 PROJECT CONDITIONS

- A. Verify before installation that interior moisture and temperature approximate normal occupied conditions.

- B. Verify that floor and wall surfaces are prepared and ready to receive cases.

3.02 INSTALLATION

- A. Deliver cases set up, made in one piece.
- B. Follow manufacturer's instructions for storage and handling of units before installation.
- C. Install level and plumb, in accordance with manufacturer's recommendations.

3.03 ADJUST AND CLEAN

- A. Verify that all accessories are installed as required for each unit.
- B. At completion of work, clean glass surfaces, back panels and trim in accordance with manufacturer's recommendations, leaving all materials ready for use.

DIVISION 10 - SECTION 10100 / DIVISION 12 - SECTION 12350

PART 1 - GENERAL

1.01 DESCRIPTION OF WORK

- A. This section includes Premiere Wall-Mounted Trophy and Display Cases
- B. This section includes Imperial Series Wall-Mounted Trophy and Display Cases
- C. This section includes Universal Series No. 333 Wall-Mounted Display Cases

1.02 REFERENCED STANDARDS

- A. ASTM-E 84
- B. ASTM B221

1.03 SUBMITTALS

- A. Shop Drawings: Provide shop drawings for each type of wall-mounted display or trophy case required.
- B. Product Data: Provide technical data for materials specified. Include Material Safety Data Sheets, when applicable.
- C. Samples:
 - 1. Manufacturer's color charts
 - 2. Composition samples of material and trim to illustrate finish, color and texture.

1.04 OPERATION & MAINTENANCE

- A. Include data on regular cleaning, stain removal, and precautions.

1.05 REGULATORY REQUIREMENTS

- A. Conform to applicable code for flame/smoke rating in tackboards in accordance with ASTM-E 84.

1.06 QUALITY ASSURANCE

- A. Provide all items in this section as manufactured by:
Claridge Products and Equipment, Inc.
Harrison, Arkansas 72602-0910
Phone: 870/743-2200; Fax: 870/743-1908

1.07 FIELD CONDITIONS

- A. Field measure prior to preparation of shop drawings and fabrication to ensure proper fit.

1.08 WARRANTY

- A. Submit a standard warranty, stating when installed in accordance with manufacturer's instructions and recommendations, Claridge trophy and display cases are guaranteed for one year against defects in materials and workmanship. Guarantee does not cover normal wear and tear, improper handling, any misuse, or any defects caused by vandalism or subsequent abuse. Guarantee covers replacement of defective material but does not include cost of removal or reinstallation.

PART 2 - PRODUCTS

2.01 MANUFACTURERS

- A. Premiere, Imperial and Universal Series Wall-Mounted Display and Trophy Cases as manufactured by: Claridge Products and Equipment, Inc., Harrison, Arkansas 72602-0910; Phone: 870-743-2200; Fax: 870-743-1908

2.02 MATERIALS

- A. Premiere Wall-Mounted Trophy and Display Cases
1. Architect to select from Claridge Cork, Fabricork, Hook-Fab, Designer Fabric and Tan Nucork tackable back panel or Walnut or Oak grained low-pressure laminate finish back panel.
 2. Standard sizes: 4' x 3'; 4'x4'; 4' x 5'; 4'x6'; 4'x8'; 4'x10'; 4'x12'; 4'x16'. Special sizes on request.
 3. Housing: Perimeter trim is 1-1/2" x 2" extruded aluminum tube; inside cabinet depth 13-3/4"; O.A. 16".
- B. Imperial Series Wall Mounted Trophy and Display Cases
1. Architect to select from Claridge Cork, Fabricork, Hook-Fab, Designer Fabric and Tan Nucork tackable back panel or Walnut or Oak grained low-pressure laminate finish back panel.
 2. Standard sizes: 3' x 4' x 7"; 4' x 5' x 7"; 4' x 6' x 7"; 4' x 5' x 10-3/4"; 4' x 6' x 10-3/4"; inside depth of 7" cases is 5-1/8"; inside depth of 10-3/4" cases is 8-7/8"
 3. Housing: Perimeter trim is 1-1/4" x 3-1/4" extruded aluminum with satin anodize finish.
 4. Header Panel: Architect to specify if 6" translucent plexiglas header required.
- C. Universal Series Wall Mounted Trophy and Display Cases (No. 333)
1. Architect to select from Tan Cork or low-pressure laminate with Oak grain finish back panel
 2. Standard size is 30" (H) x 36" (W) x 12" (D)
 3. Housing: Satin anodize perimeter trim has 1-3/4" face
 4. Angle hangers furnished
- D. Glass Doors: Glass doors are 3/16" tempered, unless otherwise specified.
1. Sliding door cases have ground-in finger pulls, doors slide on glides, and are fitted with flat key tumbler locks.
 2. Premiere cases have three 6, 8, 10 or 12-inch wide (as specified) adjustable glass shelves; 7-inch deep Imperials have 4-inch shelves; 10-3/4-inch Imperials have 8-inch shelves.
 3. Necessary brackets and shelf standards provided.
- E. Metal Trim and Accessories: Provide aluminum extrusions as manufactured by Claridge Products and Equipment, Inc. Trim shall be heavy gauge extruded aluminum and shall meet or exceed ASTM B221 Alloy Standards. Finish to be etched and anodized satin finish.
- F. Colors: As selected from manufacturer's standard colors. Over 50 standard tackboard colors to choose from. Color charts furnished on request.
- G. Options: Color anodize or powder coat finish on trim; fluorescent lights (lights not available in Universal case)

2.03 FABRICATION

- A. Shop assembly: Provide factory assembled cases to requirements indicated on shop drawings.
- B. Units shall be of dimensions shown in details and in accordance with manufacturer's shop drawings, as approved by architect.

PART 3 - EXECUTION

3.01 PROJECT CONDITIONS

- A. Verify before installation that interior moisture and temperature approximate normal occupied conditions.
- B. Verify that floor and wall surfaces are prepared and ready to receive cases.

3.02 INSTALLATION

- A. Deliver cases set up, made in one piece.
- B. Follow manufacturer's instructions for storage and handling of units before installation.
- C. Install level and plumb, in accordance with manufacturer's recommendations.

3.03 ADJUST AND CLEAN

- A. Verify that all accessories are installed as required for each unit.
- B. At completion of work, clean glass surfaces, back panels and trim in accordance with manufacturer's recommendations, leaving all materials ready for use.