

**Quartet Brand Electronic Ovonic Units for Sale by Indoff****5/10/02**

140 West Wynd Terrace  
 Middletown, CT 06457-8733  
 ahutton@ahutton.com

Phone **860-632-2026**  
 Fax **860-632-2028**  
**www. ahutton.com**

**Dropshipped from Factory to you - PC interface only - do not have built in printer**

FOB: Mississippi zip 38829 also see Webster for touch sensitive models

Freight: Freight is free for orders over \$1,200 list new policy 7/01

Dealers Welcome

Lead time: **5-10 Business days or sooner**

<u>P/n</u>	<u>Description</u>	<u>Wide x High</u>	<u>Useable</u>	<u>Freight</u>	<u>Wt</u>	<u>list</u>	<u>Sell</u>
QO4230	PC Ovonic Whiteboard	26.8"x 40.5"	24.6"x38"	UPSable	18	\$795	\$750
QO4230S**	Stand for QO4230			UPSable		\$199	\$199
QO4320	PC Ovonic Whiteboard	38" x 31"	36"x24.5"	UPSable	18	\$895	\$850
QO4320S	Stand for QO4320					\$199	\$199
QO4430	PC Ovonic Whiteboard	47" x 39.6"	45" x 35"	Truck	30	\$1,595	\$1,550
QO4430S	Stand for 4430					\$209	\$209
QO4540**	PC Ovonic Whiteboard	68" by 48"	66" x 44"	Truck	44	\$2,795	Gone
QO4540D	above+projection	68" by 48"	66" x 44"	Truck	44	\$3,195	\$3,095
QO4540S	Stand for QO4540 and QO4540D			Truck		\$495	\$495

**PC Whiteboard 4000 series \*\*Discontinued Models- may be available if Sell \$ listed**

Note all units except QO4540 interface with LCD Projectors

**System requirements:**

IBM compatible personal computer, 486-33MHz or higher

Windows 3.1, 3.11, 95 and NT (3.51 & 4.0), Windows 2000

8 MB RAM memory minimum

10 MB disk space for Windows 95 and NT 15 MB for Windows 3.1 and 3.11

One available serial port with 9- or 25-pin D-type male connector

DC input: 7.5-12V DC, 100 milli-amps or less

Operating temperature: 52C to 37C or 41F to 98F, storage temperature: -20C to 50C

Operating humidity: up to 90% non-condensing

**Included:**

Signal Interface: RS-232, 9-pin male EMI reducing serial cable (9 to 25-pin adapter also included)

Ibid Software disks to operate the whiteboard and a shareware disk to e-mail

**Features:**

Communication speed 192 pts/sec, 9600 baud

Image transfer can be achieved via OLE drag drop, clipboard or file export options

File export formats by snapshot: .BMP, .JPG, .TIF, html and .WMF

12 bit sampling, 13 bits derived

200 pts/inch or better

Overall absolute accuracy 2.5%, linearity 1.5%, repeatability 1%

Data collected and displayed in real-time on the PC

**Guarantee:**

1 year back to base

**Regulatory:**

\* CE approved

\* FCC Class B, UL/CSA, TUV

**Software Used:**

Ibid 2.1 - upgraded for free as as new versions are released