

Panasonic

KX-BP535
KX-BP635
KX-BP735



Ideal For:

- Seminars
- Meetings
- Brain Storming
- Scheduling
- Training
- Copying Charts and Graphs

PanaboardTM
Plain Paper Printing

Features & Benefits

- *Panaboards come with an integrated printer for easy plain paper printing with multiple copies*
- *With the optional PC Interface software, Panaboard printer can print from a PC*
- *Increases audience attention and participation*
- *Helps presenters give clear notes on the meeting to everyone, increasing efficiency and reducing meeting time*
- *All models can be wall-mounted or used with an optional stand*

View the Control Panel from a PC



Panasonic's new Plain Paper Panaboard interfaces with your PC. It comes complete with a Windows 95/98/NT printer driver.



Slim Modular Design

- Paper tray holds 80 sheets of paper
- Roll of thermal transfer film prints approx. 300 pages
- Confidentiality when printing because a special coating is placed on the film that prevents it from being photocopied



Model Number	KX-BP535	KX-BP635	KX-BP735
Panel Size	2' 11 7/16" H x 4' 7 1/8" W	2' 11 7/16" H x 6' 1 1/3" W	2' 11 7/16" H x 4' 7 1/8" W
Copying Area	2' 9 15/32" H x 4' 4 3/8" W	2' 9 15/32" H x 5' 6 5/32" W	2' 9 15/32" H x 4' 4 3/8" W
Number of Panels	2 Continuous	2 Continuous	4 Continuous
Scanning System	CCD Flat-Scan	CCD Flat-Scan	CCD Flat-Scan
Printing System	Fusion Thermal Transfer	Fusion Thermal Transfer	Fusion Thermal Transfer
Paper Size	8 1/2" x 11"	8 1/2" x 11"	8 1/2" x 11"
Copy Density	Approx. 203 dots/inch (8 dots/mm)	Approx. 203 dots/inch (8 dots/mm)	Approx. 203 dots/inch (8 dots/mm)
Number of Copies	1 – 9	1 – 9	1 – 9
Copy Speed	15 Seconds	15 Seconds	15 Seconds
Weight (Without Stand)	75 lbs. (34 kg)	80.5 lbs. (36.5 kg)	84.9 lbs. (38.5 kg)
Dimensions (HxWxD) (Without Stand)	4' 7 1/8" x 5' 1 1/32" x 9 7/16"	4' 7 1/8" x 6' 3 9/32" x 9 7/16"	4' 7 1/8" x 5' 4 3/4" x 9 7/16"
(With Stand)	6' 1 13/16" x 5' 1 1/32" x 1' 11 1/4"	6' 1 13/16" x 6' 3 9/16" x 1' 11 1/4"	6' 1 13/16" x 5' 4 3/4" x 1' 11 1/4"
Power Supply	AC 100–120V, 50/60Hz	AC 100–120V, 50/60Hz	AC 100–120V, 50/60Hz
Power Consumption	2.2 A (Operational) 0.1 A (Standby)	2.2 A (Operational) 0.1 A (Standby)	2.2 A (Operational) 0.1 A (Standby)
Accessories			
Replacement Film*1	KX-BP081 / KX-BP082	KX-BP081 / KX-BP082	KX-BP081 / KX-BP082
Marker Kit*2	KX-B035	KX-B035	KX-B035
Options			
Stand	KX-B061M	KX-B061M	KX-B061M
Wall Mounting Kit	KX-B063	KX-B063	KX-B063
Ruler Kit	KX-B05	KX-B05	KX-B05
PC Interface Kit*3	KX-BP095	KX-BP095	KX-BP095

*1 Thermal Transfer Replacement Film: KX-BP081 (contains two 100m rolls); KX-BP082 (contains one 100m roll and one film cassette).

*2 KX-B035 Marker Kit (contains 1 each: black, blue and red markers & 1 eraser).

*3 KX-BP095 includes the Interface Board, Cable, Software (including a Print Driver Diskette).

Note: Each Panaboard includes three markers (black, red and blue), an eraser and a roll of thermal transfer film. Design and specifications are subject to change without notice.

Panaboard™