

Multi-Function Control Panel

The Panaboard control panel has been designed for simplicity. All functions, including contrast and number of copies, can be accessed with one touch convenience.



Advance/Reverse

All models offer reverse screen keys, KX-B730 includes both advance and reverse keys.



2-Screen Copy (except KX-B730)

Allows users to copy two Panaboard screens (front and back) onto one sheet of paper.



Multi-Copy Key

Enables up to 9 copies by one touch control, returning to original screen after printing.



Contrast Indicator

Indicator on: Darker / Indicator off: Normal

Dual-Source Copying

At the push of a button, Panaboard can copy whatever has been written or drawn. It can even print an image that's been taped to the screen!

Thermal Printing with Auto-Cutter

Panaboards utilize easy-to-load thermal paper with automatic cutting. The CCD image sensor provides a clear 203 dots per inch copy density.

Options

Printer Interface Board

Allows for plain paper output by connecting directly to your PCL 4/PCL 5 compatible printer.

PC Interface Software

Enables downloading of all images to a PC. Everything written on the Panaboard can be saved as a Bitmap or TIFF file; great for archiving, e-mailing, PC faxing or networking all your images!

Ruler Kit

Draw straight lines horizontally and vertically!

Model	KX-B430	KX-B530	KX-B630	KX-B730
Panel Size	2' 11 7/16" H x 2' 7 1/2" W	2' 11 7/16" H x 4' 7 1/8" W	2' 11 7/16" H x 6' 1 1/3" W	2' 11 7/16" H x 4' 7 1/8" W
Copying Area	2' 9 15/32" H x 2' 4 3/4" W	2' 9 15/32" H x 4' 4 3/8" W	2' 9 15/32" H x 5' 6 5/32" W	2' 9 15/32" H x 4' 4 3/8" W
Number of Panels	2 Continuous	2 Continuous	2 Continuous	4 Continuous
Copying System	CCD Image Sensor, Thermal Print Head	CCD Image Sensor, Thermal Print Head	CCD Image Sensor, Thermal Print Head	CCD Image Sensor, Thermal Print Head
Paper Size	8 1/2" x 11"	8 1/2" x 11"	8 1/2" x 11"	8 1/2" x 11"
Copy Density	Approx. 203 dots/inch (8 dots/mm)	Approx. 203 dots/inch (8 dots/mm)	Approx. 203 dots/inch (8 dots/mm)	Approx. 203 dots/inch (8 dots/mm)
Number of Copies	1 – 9	1 – 9	1 – 9	1 – 9
Copy Speed	20 Seconds	15 Seconds	15 Seconds	15 Seconds
Weight	61 lbs. (27.5 kg)	74 lbs. (33.5 kg)	81.5 lbs. (37 kg)	77.2 lbs. (35 kg)
Dimensions (Without Stand)	4' 9 3/32" H x 3' 1 13/32" W x 9 5/32" D	4' 9 3/32" H x 5' 1 1/32" W x 9 5/32" D	4' 9 3/32" H x 6' 3 9/16" W x 9 5/32" D	4' 9 3/32" H x 5' 4 3/4" W x 9 5/32" D
(With Stand)	6' 10 11/16" H x 3' 3 3/16" W x 1' 11 1/4" D	6' 10 11/16" H x 5' 1 1/32" W x 1' 11 1/4" D	6' 10 11/16" H x 6' 3 9/16" W x 1' 11 1/4" D	6' 10 11/16" H x 5' 4 3/16" W x 1' 11 1/4" D
Options				
Stand	KX-B062M	KX-B061M	KX-B061M	KX-B061M
Wall Mounting Kit	KX-B063	KX-B063	KX-B063	KX-B063
Ruler Kit	KX-B05	KX-B05	KX-B05	KX-B05
Printer Interface Board	KX-B09-V4	KX-B09-V4	KX-B09-V4	KX-B09-V4
PC Interface Software*	KX-B091	KX-B091	KX-B091	KX-B091
Marker Kit (1 ea: Black, Blue and Red Markers & Eraser)	KX-B035	KX-B035	KX-B035	KX-B035

*For PC connectivity, both the KX-B091 and KX-B09-V4 are necessary.

Note: Each Panaboard includes three markers (black, red and blue), an eraser and a starter roll of paper. Design and specifications are subject to change without notice.