Print Direct to Flexible Magnet



A quick, low cost solution for your display and signage needs!

Step One

Choose Which PrintMagnet™ Works for Your Application

PrintMagnet™:

- · For dye and pigment based inkjet printers
- High quality, matte white or photo quality finish on the printable side
- For indoor applications only

$PrintMagnetVinyI^{TM}$:

- For solvent and eco-solvent inkjet printers
- High quality, matte white or photo quality finish on the printable side
- For outdoor and indoor applications

Product Description	Min. Magnetic Pull/Lbs. Per Sq. Ft.	Approx. Shipping Wt./Per 200 Sq. Ft. Roll
12 mil White Paper	30	49
12 mil White Vinyl	30	49
15 mil White Paper	40	61
15 mil White Vinyl	40	61 .
20 mil White Paper	60	79
20 mil White Vinyl	60	79
25 mil White Vinyl	70	98
30 mil White Vinyl	85	130

Step Two

Choose a Thickness for Your Application

Typical thickness options are shown on the chart below. Custom thicknesses and tolerances may be special ordered. Thicknesses .012" and greater are available in rolls. Custom pre-cut sheet thicknesses range from .008" to .060"

Step Three

Choose a PrintMagnet™ Final Size

PrintMagnet™ and PrintMagnetVinyl™ can be cut into sheets, slit into rolls or diecut. Provide detailed information and our expert technicians will provide you with what you need.

- Custom cut sheets
- Pre-cut 8.5" x 11" die-cut sheet
- 24.275" wide rolls that can be cut to the size you need
- 8.5" x II" die-cut sheets that are perforated to yield 10 business cards (2" x 3.5")
- Pre-cut 4" x 6" photo quality sheets
- Pre-cut 4" x 6" matte white sheets